

SAFETY DATA SHEET



Date Prepared : 11/10/2015
SDS No : HP32 PART B

STICK-IT TWO PART URETHANE ADHESIVE PART B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: STICK-IT (Part B)

GENERAL USE: Polyurethane curative

MANUFACTURER

Soft Jamb Co.
6298 Mt. Pinos Ct
Alta Loma, CA 91701
Emergency Phone: (909) 720-0909

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC: (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Skin Irritation, Category 2
Eye Irritation, Category 2A
Skin Sensitization, Category 1

GHS LABEL

Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.
H319: Causes serious eye irritation.
H317: May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS**Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P362+P364:
Take off contaminated clothing and wash it before reuse.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.

STICK-IT TWO PART URETHANE ADHESIVE PART B**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Avoid eye and skin contact. Avoid breathing vapors. Causes eye and skin irritation. Use in well ventilated areas.

POTENTIAL HEALTH EFFECTS

EYES: Causes serious eye irritation.

SKIN: Causes skin irritation. May cause an allergic skin reaction.

INGESTION: May be harmful if swallowed.

INHALATION: May be harmful if inhaled.

MEDICAL CONDITIONS AGGRAVATED: Pre-existing skin conditions may be aggravated by exposure.

ROUTES OF ENTRY: Eye and skin contact, inhalation of vapors, or accidental ingestion.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Polyether polyol mixture	60 - 100	Proprietary
Hydroxy terminated poly(oxyalkylated) polyol	10 - 30	102-60-3
Tetraethylenepentamine	1 - 5	112-57-2
Silica, Amorphous, Fumed	1 - 5	112945-52-5

4. FIRST AID MEASURES

EYES: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

INGESTION: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

NOTES TO PHYSICIAN: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, and nitrogen oxides.

FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

FIRE FIGHTING EQUIPMENT: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

LARGE SPILL: Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

STICK-IT TWO PART URETHANE ADHESIVE PART B**ENVIRONMENTAL PRECAUTIONS**

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

RELEASE NOTES: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

HANDLING: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

STORAGE: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

STORAGE TEMPERATURE: 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

STICK-IT TWO PART URETHANE ADHESIVE PART B

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
Polyether polyol mixture	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE
Hydroxy terminated poly(oxyalkylated) polyol	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE
Tetraethylenepentamine	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE
Silica, Amorphous, Fumed	OSHA PEL	TWA	NE	NE
		STEL	NE	NE
	ACGIH TLV	TWA	NE	NE
		STEL	NE	NE
	Supplier OEL	TWA	NE	NE
		STEL	NE	NE

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

STICK-IT TWO PART URETHANE ADHESIVE PART B

EYES AND FACE: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

SKIN: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

RESPIRATORY: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

PROTECTIVE CLOTHING: Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

WORK HYGIENIC PRACTICES: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Slight amine

COLOR: Pale yellow

pH: Not Established

PERCENT VOLATILE: 0.03

FLASH POINT AND METHOD: > 160°C (320°F) Pensky-Martens CC

VAPOR PRESSURE: Not Established

VAPOR DENSITY: Not Established

BOILING POINT: Not Established

SOLUBILITY IN WATER: Slightly soluble

SPECIFIC GRAVITY: 1.038 (water=1) at 25°C (77°F)

VISCOSITY #1: 2590 Centipoise at 25°C (77°F)

(VOC): < 0.320 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. STABILITY AND REACTIVITY

REACTIVITY: Hazardous reactions will not occur under normal transport or storage conditions.

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

STABILITY: This product is stable under normal ambient conditions of temperature and pressure.

CONDITIONS TO AVOID: High temperatures, moisture, and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and nitrogen oxides.

INCOMPATIBLE MATERIALS: Isocyanates, acids, and strong oxidizers.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Polyether polyol mixture	Not Established	Not Established	Not Established
Hydroxy terminated poly(oxyalkylated) polyol	3280 mg/kg	> 2000 mg/kg	Not Established
Tetraethylenepentamine	2140 mg/kg	> 660 mg/kg	Not Established
Silica, Amorphous, Fumed	5000 mg/kg	Not Established	2.08 mg/l

STICK-IT TWO PART URETHANE ADHESIVE PART B

SKIN CORROSION/IRRITATION: Causes skin irritation.

SERIOUS EYE DAMAGE/IRRITATION: Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION: May cause sensitization by skin contact.

GERM CELL MUTAGENICITY: No data available.

CARCINOGENICITY

NOTES: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

REPRODUCTIVE TOXICITY: No data available.

STOT-SINGLE EXPOSURE: No data available.

STOT-REPEATED EXPOSURE: No data available.

ASPIRATION HAZARD: No data available.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available.

ECOTOXICOLOGICAL INFORMATION: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

BIOACCUMULATION/ACCUMULATION: No data available.

DISTRIBUTION: No data available.

CHEMICAL FATE INFORMATION: No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated

VESSEL (IMO/IMDG): Not Regulated

COMMENTS: Not dangerous according to transport regulations.

STICK-IT TWO PART URETHANE ADHESIVE PART B

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health hazard. Chronic health hazard

313 REPORTABLE INGREDIENTS: This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675): None

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product does not contain any chemicals subject to TSCA Section 12(b) export notification.

TSCA STATUS: This product or its components are listed in or exempt from the TSCA inventory requirements.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119—PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5).

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

GENERAL COMMENTS: No data available.

16. OTHER INFORMATION


REASON FOR ISSUE: New Issue

Date Prepared: 11/10/2015

HMIS RATING

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION	D	

NFPA CODES



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Soft Jamb Co.. The data on this sheet relates only to the specific material designated herein. Soft Jamb Co. assumes no legal responsibility for use or reliance upon this data.